



CUSTOMER NAME	客户名称:	
CUSTOMER NO.	客户编号:	
SERIES	系 列:	拨动开关大电流系列
MODEL NO.	型 号:	XB-H25-0823PA-8NT3BB
DRAWING NO.	图 形 号:	Sliding switch high current series

依据和存档之用，多谢合作！

APPROVE 接受			NOT APPROVE 不接受		
SIGNATURE 簽署	STAMP 盖章	DATE 日期			

PREPARED BY.制表人	CHECKED BY.校对	APPROVED BY.审核	APPROVAL BY. 批准
研发部 戴海明 2022. 06. 08	品质部 黄自清 2022. 06. 08	工程部 庞军 2022. 06. 08	总经办 吴量 2022. 06. 08

Quality core! Afterburner for Made in China!

				E		F		G		H	
REV.		ECN NO.		DATE		DESCRIPTION		CHANGE BY		APPROVED BY	
版本		ECN编号		日期		内容描述		变更人		核准	
A0		/		19/04/09		NEW RELEASE				JIMMY	
规格 Specification:											
1.开关型号 Model No.: XB-H25-0823PA-8NT3BB											
2.额定值 Rating:8A 125/250VAC											
3.接触电阻 Contact resistance:≤30 mΩ											
4.绝缘电阻 Insulation resistance:≥100 MΩ(DC500V/Min)											
5.电气寿命 Electronics life:＞10000 cycles											
6.操作力 Operation force:500±200gf											
7.所有材料符合Rohs要求 All materials are Rohs compliant											

A		B		C		D	
1		30.5		14.2			
2		30.5		14.2			
3		7.8		6.0±0.2 Travel			
4		6.2		3.0			
5		6.4		6.4			
6		6.4		6.4			
A		B		C		D	

DRAWN BY		Jimmey		190409		SCALE		FREE		PRODUCT NAME	
制 图		Jimmey		190409		比 例		1/1		SLIDE SWITCH	
CHECKED BY		Jimmey		190409		PAGE		1/1		DESCRIPTION	
核 对		Jimmey		190409		UNIT		mm		2P3T 8A 125/250VAC	
APPROVED BY		批 准		批 准		PROJECTED		投影		PART NO.	
批 准		批 准		批 准		投影		投影		XB-H25-0823PA-8NT3BB	
TOLERANCE		5 < L ≤ 5		±0.1		角 度		±2°		DRAWN NO.	
未标注公差		L > 30		±0.3		角 度		±2°		HTDW20190409-012	
E		F		G		H					





X 东莞市溪榜电子有限公司		DONG GUAN XI BANG ELECTRONI CS CO., LTD.	
5.5		8.0	
0.5		8.2	
6.2		6.2	
CIRCUIT		CIRCUIT	
5		6	
6		7	
A		B	


XB 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.		文件编号	XB2019031901		
		发行日期	2019 年 3 月 19 日		
H25 Series Specification H25 滑动开关规格书		编 制	Paul	审 核	Jimmy
		版 本	B	页 面	1/3
1. General 一般描述					
1.1 Part Name		H25 Series Slide Switch			
产品名称		H25 系列滑动开关			
1.2 Operating Temperature		0℃~85℃			
使用环境温度					
1.3 Function 功能		See attached drawing 见附件图纸			
1.4 Standard Testing Condition		Normal Temperature 25±10℃ / Normal humidity 45~85%RH			
测试条件		Normal atmospheric pressure 860~1060hPa			
		温度 25±10℃/湿度 45~85%RH/大气压力 860~1060hPa			
1.5 Appearance		See attached drawing			
外观		见附件图纸			
2. Approval/Rating 认证/规格					
Approval 安规认证		Rating 规格参数		Electronics life 电气寿命	
UL、TUV		3(3)A 125/250VAC μ T85		10,000 Cycles	
				Approved	
3. Electronical Characteristics 电气特性					
NO. 序号	Item 项目	Condition 条件		Criteria 标准	
3.1	Electrical life 电气寿命	10,000 life cycles 10,000 周次		Switch perform 10 cycles of normal function after max. electrical life 开关达到最大电气寿命后能继续运行 10 次	
3.2	Contact resistance 接触阻抗	Initial 起始		≧30mΩ	
3.3	Insulation resistance 绝缘阻抗	Between terminals to case at 500VDC for 1minute 脚与外壳间承受 500VDC,保持 1 分钟		≧100MΩ	
3.4	Dielectric strength 耐压强度	Between terminals of contacts 1000VAC, 5mA for 1 minute 端子与端子间承受 1000VAC, 5mA,保持 1 分钟 Between terminals to button 1500VAC, 5mA for 1 minute 端子与外壳间承受 1500VAC, 5mA,保持 1 分钟		No flash or dielectric breakdown 无闪光或击穿现象	



H25 Series Specification H25 滑动开关规格书

4. Physical characteristics 物理特性

NO. 序号	Item 项目	Condition 条件	Criteria 标准
4.1	Mechanical life 机械寿命	Perform 50,000 cycles operations 50,000 周次	No detachable parts & switch / normal function 开关无损坏/功能正常
4.2	Operating force 操作力 Operating mode 操作方式	Correct operation 正确操作  Improper operation 非正确操作 	Operating force: See attach drawing 操作力: 见附件图纸 Correct operation: Horizontal force push pull the slider 正确操作: 水平力推动滑块 Improper operation: Non horizontal force push pull the slider 非正确操作: 非水平力推动滑块 Improper operation will affect the switch function 非正常操作将造成开关功能不良
4.3	Travel 行程		See attached drawing 见附件图纸
4.4	Terminal strength 端子强度	Pulling & pushing force of max.3Kg apply to the terminal vertically 端子最大能承受 3Kg 垂直拔出/推入力 	No detach of terminal 端子无推入及脱离现象

 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONI CS CO., LTD.		文件编号		XB2019031901		
		发行日期		2019 年 3 月 9 日		
H25 Series Specification H25 滑动开关规格书		编 制		LeeM	审 核	Jimmy
		版 本		B	页 面	3/3
4.5	Solder ability of terminals 端子可焊性	Soldering temperature: 230±5℃ 焊接温度 230±5℃ Soldering time: 3±0.5 seconds 焊接时间 3±0.5 秒		Solder should cover minimum 50% of soldering surface 焊料最少覆盖 50%焊接表面		
4.6	Hand soldering 手工焊接	Please practice according to bellow conditions: 请按以下条件进行焊接: Soldering temperature :≤350℃ 焊锡温度: ≤350℃ Continuous soldering time:≤3 Sec 连续焊接时间: ≤3 Sec				
4.7	Automatic flow soldering 自动焊接	For the product of DIP ,type solder according to the following conditions 对于 DIP 产品, 请按以下条件进行焊接 Soldering temperature :≤260±5℃ 焊锡温度: ≤260±5℃ Continuous soldering time: ≤3 Sec 连续焊接时间: ≤3 Sec				
		For the product of SMT ,type solder according to the following conditions 对于 SMT 产品, 请按以下条件进行焊接 surface of product temperature 部品表面温度 (℃)  time inside soldering equipment 炉内通过时间				
4.8	Flammability rating 防火等级	Thermoplastic UL 94V-0 热塑性塑料 UL 94V-0				

If the special or particular requirement are not shown in the specification, please contact our company representative for further explanation.

若在规格书内未有注明的规格, 请联系本公司的销售代表以获取详细解释。

This specification is subjected to change without prior notice.

此规格书如有更改, 恕不另行通知