



REV NO./版次	REVISION NOTE/修订注释	DATE/日期	SIGNATURE/签名

ELECTRICAL CHARACTERISTICS

1. RATING: DC 30V 0.5A
2. CONTACT RESISTANCE: $100\text{m}\Omega$ MAX
3. INSULATION RESISTANCE: $100\text{M}\Omega$ MIN
4. DIELECTRIC STRENGTH: AC 250V (50~60Hz)/60S

MECHANICAL CHARACTERISTICS

1. PRACTICAL TEMPERATURE RANG: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
2. OPERATING FORCE: $180 \pm 50\text{gf}$
3. MECHANICAL LIFE: 10,000 cycles

NO.	PART NAME	MATERIAL	QTY.	FINISHING
9	CONTACTPIECE-2	SUS	1	NATURAL
8	CONTACTPIECE-1	SUS	1	NATURAL
7	TERMINAL	BRASS STRIP	6	Ag PLATED
6	CASE	PA66	1	GRAY
5	LOCK PIN	SUS WIRE	1	NATURAL
4	SPRING	SUS WIRE	1	NATURAL
3	CONTACT	BRONZE	2	Ag PLATED
2	KNOB	PBT	1	WHITE
1	COVER	PA66	1	BLACK

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

GENERAL TOLERANCE 未指的公差		TITLE 名称	
X. ± 0.5	X. $^{\circ} \pm 5^{\circ}$	XB-5858P-2PL	
.X ± 0.3	.X $^{\circ} \pm 2^{\circ}$	PART NO. 零件编号	
.XX ± 0.2	.XX $^{\circ} \pm 1^{\circ}$	DWG NO. 图纸编号	
.XXX ± 0.1	.XXX $^{\circ} \pm 0.5^{\circ}$	XB-5858P-2PL	
APPROVAL 审批	CHECKED 核准	DRAWN 设计	UNIT 单位 (mm)
			SCALE 比例
			1:1
			PROJ.
			REV.