



9	10	11	12
REV NO/版次	REVISION NOTE/修订注释	DATE/日期	SIGNATURE/签名

**ELECTRICAL CHARACTERISTICS**

1. RATING: DC 30V 0.1A
2. CONTACT RESISTANCE: 100mΩ MAX
3. INSULATION RESISTANCE: 100MΩ MIN
4. DIELECTRIC STRENGTH: AC 250V (50~60Hz)/60S

**MECHANICAL CHARACTERISTICS**

1. PRACTICAL TEMPERATURE RANG: -40℃~+85℃
2. OPERATING FORCE: 250±50gf
3. MECHANICAL LIFE: 20,000 cycles

8				
7	SHELL	PA66	1	BLUE
6	TERMINAL	BRASS STRIP	6	Ag PLATED
5	CASE	PA66	1	BLACK
4	SPRING	SUS WIRE	1	NATURAL
3	CONTACT	BRONZE	2	Ag PLATED
2	KNOB	PA66	1	BLUE
1	COVER	PA66	1	BLACK
NO.	PART NAME	MATERIAL	QTY.	FINISHING

**XGB** 东莞市溪榜电子有限公司  
DONG GUAN XI BANG ELECTRONI CS CO., LTD.

GENERAL TOLERANCE 未指的公差		TITLE		
X. ± 0.5	X.° ± 5°	名称 <b>XB-7272-L</b>		
.X ± 0.3	.X° ± 2°	PART NO. 零件编号		DWG NO. 图纸编号
.XX ± 0.2	.XX° ± 1°			<b>XB-7272-L</b>
.XXX ± 0.1	.XXX° ± 0.5°			
APPROVAL 审批	CHECKED 核准	DRAWN 设计	UNIT 单位 (mm)	SCALE 比例
		WEIMIN SU		1:1
				PROJ.  REV.