

REV.	ECN. NO.	APPD.

Top view of the connector showing dimensions 8.84, 10.24, 1.00, and 1.50. Callouts ② and A are present.

Top view of the connector showing dimensions 8.94, 10.04, 0.50, and 2.00. Callouts ② and A, and radius R0.20 are present.

Front view of the connector showing dimensions 4.46, 3.06, 1.50, and 1.00. Callouts A1, A12, B12, and B1 are present.

Side view of the connector showing dimensions 4.46, 3.06, 1.50, and 1.00.

Front view of the connector showing dimensions 4.06, 3.16, 2.00, and 0.50. Callouts R0.20 and R1.70 are present.

Side view of the connector showing dimensions 4.06, 3.16, 2.00, and 0.50. Callouts R0.20 and R1.70 are present.

Bottom view of the connector showing dimensions 10.24 and 4.46.

Detail view of the connector showing dimensions 0.97 and 0.70. Radius R0.35 is indicated.

X.	± 0.50	X.*	± 2°	UNITS	mm	XIB 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	PART NO. (INTENDED USE)	TITLE: TYPE C USB 24Pin SMT (1.6mm Type C USB)	
.X	± 0.30	.X.*	± 1°	MAT'L					
.XX	± 0.10	.XX.*	± 0.5°	FINISH	APPD:	DWG NO:	XIB-M15-M		
.XXX	± 0.05			Q'TY	CHKD:			SCALE	SHEET
						DR: Steven.Xie 2021/09/07	1/1	1/1	A1

REV.	ECN. NO.	APPD.

X.	± 0.50	X.*	± 2°	UNITS mm	XIB 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	PART NO. (INTENDED USE)	TITLE: TYPE C USB 24Pin SMT (1.6mm Type C USB)	
.X	± 0.30	.X.*	± 1°					
.XX	± 0.10	.XX.*	± 0.5°	MAT'L	APPD:	CHKD:	DWG NO:	
.XXX	± 0.05							
				FINISH	DR: Steven.Xie 2021/09/07	XB-M15-M		
				Q'TY		SCALE	SHEET	REV.
						1/1	1/1	A1