



标注: ①-⑧为重点检测尺寸

Technical characteristics

SPECIFICATION: 5 A max. @ 125 VAC.
 2 A max. @ 250 VAC.
 MECHANICAL LIFE: 40,000 make-and-break cycles.
 ELECTRICAL LIFE: 10,000 make-and-break cycles.
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC
 100mA for both silver.
 INSULATION RESISTANCE: 1000 MΩ min.
 DIELECTRIC STRENGTH: 1500 VAC min.
 OPERATING TEMPERATURE: -30°C to +85°C.

Materials

CASE: PPA (UL 94V-0)
 HOUSING: Stainless Steel.
 ACTUATOR: Alloy, chrome plated.
 BUSHING: Alloy, nickel plated.
 CONTACT/TERMINALS: Copper alloy silver plated.
 RoHS

手柄位置及导通端子示意图

Model NO.	POS. 1	POS. 2	POS. 3
202	ON	NONE	ON
SCHEMATIC		N/A	

XB 东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

				公差 TOLERANCES	. X ± 0.4 . XX ± 0.25	角度	± 5°	UNIT 单位 mm	SCALE 1:1	
				版本 VERSION	A0	比例尺 SCALE	NONE	TITLE 图名	TOGGLE SWITCH	
				核准		日期 DATE	2023. 2. 7	DWG NO. 料号		
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY		绘图 DRAWN BY	WSL	PART NO. 型号	XB-MT-1-202-C004-N004-RS	