



标注: ①-⑦尺寸的重点检验尺寸

### Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.  
 1.5 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1000 VAC min.  
 OPERATING TEMPERATURE: -25°C to +85°C.

### Materials

CASE: PPA (UL 94V-0)  
 HOUSING: Stainless Steel.  
 ACTUATOR: Alloy, chrome plated.  
 BUSHING: Alloy, nickel plated.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS & lead-free

### 手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
102	ON	NONE	ON
SCHEMATIC		NONE	

**东莞市溪榜电子有限公司**  
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

				公差 TOLERANCES	.X± 0.4 .XX± 0.25	角度	± 5°	UNIT 单位 mm	SCALE 1:1	
				版本 VERSION	A0	比例尺 SCALE	NONE	TITLE 图名	Sub-Miniature Toggle Switch	
				核准		日期 DATE	2021. 7. 23	DWG NO. 料号	SM00087ZNR	
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY		绘图 DRAWN BY	WSL	PART NO. 型号	XB--ST-0-102-A01-T000-LF	