



标注: ①-⑥ 尺寸的重点检验尺寸

手柄位置及导通端子示意图

| | POS. 1 | POS. 2 | POS. 3 |
|-----------|--------|--------|--------|
| Model NO. | | | |
| 102 | ON | NONE | ON |
| SCHEMATIC | | N/A | |

Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.

1 A max. @ 250 VAC.

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RESISTANCE: 20mΩ max. initial @ 2-4VDC
100mA for both silver.

INSULATION RESISTANCE: 1000 MΩ min.

DIELECTRIC STRENGTH: 1000 VAC min.

OPERATING TEMPERATURE: -30°C to +85°C.

Materials

CASE: PPA (UL 94V-0)

HOUSING: Stainless Steel.

ACTUATOR: Alloy, chrome plated.

BUSHING: Alloy, nickel plated.

CONTACT/TERMINALS: Copper alloy silver plated.

RoHS

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

| 公差 TOLERANCES | | .X± 0.4 .XX± 0.25 | | 角度 | ± 5° | UNIT 单位 | mm | SCALE 1:1 | |
|---------------|-------------------------|-------------------|---------|----------------|---------------|-------------|-----|-------------|-----------------------------|
| 版本 VERSION | 变更说明 CHANGE DESCRIPTION | 日期 DATE | ECN NO. | 核准 APPROVED BY | 核对 CHECKED BY | 绘图 DRAWN BY | WSL | TITLE 图名 | Sub-Miniature Toggle Switch |
| | | | | | | | | DWG NO. 料号 | |
| 版本 VER. | 变更说明 CHANGE DESCRIPTION | 日期 DATE | ECN NO. | 核准 APPROVED BY | 核对 CHECKED BY | 绘图 DRAWN BY | WSL | PART NO. 型号 | XB-ST-0-102-C02-T002-RS |