





NOTE:
Rating: DC 12V 50mA
Operating Force: 200±100gf
Lifetime: 10,000 Cycles

PAPT NO	L
SS-3235D-03-L1	2.0
SS-3235D-03-L2	3.0
SS-3235D-03-L3	4.0



ITEM	PAPT NAME	TER,NO	QTY	MATERIAL	FINISHING	REMARK
5	Terminal	—	3	Brass (0.30t)	ag Plated	
4	Contact spring	—	1	Phosphor branze	ag Plated	
3	Base	—	1	Pa46	Black	
2	Cover	—	1	Sus	Natural	
1	Keystake	—	1	Pa46	Black	

				ANGLAR	±5°
				L ≤ 4	±0.2
				4 < L ≤ 16	±0.3
				16 < L ≤ 63	±0.4
	DATE	REVISED	APPROVED	L > 63	±0.5
				UNSPECIFIED TOLERANCES	
www.alpsr.com www.gdxidz.com www.xbswitch.com					



DSND		SCALE: N/A	MODEL TYPE: SLIDE SWITCH
DWN		VIEW:	PART NO.: SS-3235D-03-X
CHKD		UNIT: mm/in	DWG NO.:
APPD		SIZE: A4	
		WEIGHT	SHEET
			1/1
		REVISIC	A0

DONG GUAN XI BANG ELECTRONIC CO., LTD