


NOTES:
 1.RATING: 12VDC 50mA
 2.CONTACT RESISTANCE: 100mΩ Max
 3.INSULATION RESISTANCE: 100MΩ 250VDC FOR 1MIN
 4.DIELECTRIC STRENGTH: 250VAC(50/60Hz) FOR 1MIN
 5.LIFE TEST:100,000 CYCLES
 6.OPERATION FORCE&TRAVEL: SEE SPECIFICATION



REV	DESCRIPTION	DRW	DATE
A	NEW	MM	2012-5-16

6	LED	BRONZE PLATED SILVER
5	COVER	PC/PET
4	PUSH BUTTON	PA66
3	SPRING PLATE	PBS SILVER CLAD
2	CASE	PA66
1	TERMINAL	SILVER PLATED BRONZE
NO.	PART NAME	MATERIAL

LED COLOR									
1	2	3	4	5	6	12	13	14	23
Red	Yellow	Green	Blue	White	Pure Green	Red Yellow	Red Green	Red Blue	Yellow Green

XB 东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE				PART NO.:		TITLE	TACT SWITCH	
UNLESS OTHERWISE STATED				带灯开关		MODEL	XB-TS-LED-HF01-301M	
X.X	±0.25	mm	±0.5°	DRAWN	DATE	MATL		
X.XX	±0.1	UNIT	mm	MM	2012.05.16	FINISH		
REV	A	SCALE	4:1	CHK'D	DATE			
SIZE	A4	SHEET	1 OF 1	MM	2012.05.16			

