



REV.	ECN NO.	REVISED	DATE

NOTE:

1.MATERIAL:

- a.HOUSING:PBT UL94V-0
- b.CONTACT:BRASS
(SURFACE PLATING: Sn100u"-120u")
SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C~ +85°C


ORDERING INFORMATION

电池座系列

DIP 90° TYPE

PLATING:
A-Au1U"
J-Ni100U"~120U"
K-Sn100U"~120U"

MATERIAL:
1A-PBT BLACK
1B-PA66 BLACK
2A-PPA BROWN
2B-PPA BLACK
3A-PPS BROWN
3B-PPS BLACK
4A-LCP WHITE
4B-LCP BLACK



PCB Layout Diagram
Top View

UNLESS OTHERWISE SPECIFIED TOLERANCES		XG 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	
DECIMALS:	ANGLES:	DSND	DATE 2017-07-16
X : ±0.30	X : ±1°	CHKD	DATE 2017-07-16
X.X : ±0.25	X.X : ±0.5°	APVD	DATE 2017-07-16
X.XX : ±0.20		SCALE: 2:1	SIZE: A4
X.XXX : ±0.10		UNIT: mm	REV.: A/0
WEIGHT: 1.8g		VIEW:	OBJECT: MY
SHEET 1 OF 1		DRAW NO.:	

NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
3	TERMINAL(-)	1	BRASS, T=0.60mm	Sn-Plating
2	TERMINAL(+)	1	BRASS, T=0.60mm	Sn-Plating
1	HOUSING	1	PBT	BLACK