


VIEW A-A'

SPECIFICATIONS

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. RATING: DC 20V 3A MAX
 - 1-2. CONTACT RESISTANCE: 20m Ω MAX(INITAL)
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 - 1-4. INSULATION RESISTANCE: 100M Ω MIN, MEASURED BY 500V DC
2. LIFE TEST: MECHANICAL LIFE TEST 10,000 CYCLES MIN
3. TEMPERATURE RISE : 30°C MAX



P.C.B LAYOUT



CIRCUIT

版本REV.	更新标记REVISION	NOTE	日期DATE	未注公差	TOLERANCE
				X.	± 0.35
				X.X	± 0.25
绘制DRAWN				X.XX	± 0.15
设计DES'D	付坚强			X.XXX	± 0.05
审核CHK'D	叶泽奇			视图方法 PROJECTION	
批准APPV'D	彭继华				
				比例SCALE:	

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD

品名ARTICLE:
电池连接器

图号MODEL:
XB-BC-245-1P-D

单位UNIT: mm

页码SHEET: 共1页 第1页