



**Rating :**  
 15A 250V AC UL cUL  
 10A 250V AC VDE 3C KC  
**Insert And Extract Force:** 20N~50N  
**Terminal Strength:** ≥60N  
**Operating Life:** ≥6000 cycles  
**Withstand Voltage:** Between all terminals:2500VAC (50-60Hz)1min  
 terminals to Base:3750V AC (50-60Hz)1min  
**Leakage Current :** 1mA  
**Insulation Resistance:** ≥100MΩ 500V DC  
**Body Materil:** PBT 94V-2~0

序号	名称	材料	处理	数量	备注
1	DB-14-1塑料件	PBT	黑色	1	
2	DB-14-FL长插销	黄铜	镀锡	1	Plating Thickness 40u" -80u"
3	DB-14-FS短插销	黄铜	镀锡	2	Plating Thickness 40u" -80u"

46\*46\*24.5cm箱, 100只\*20袋装=2k件, 净重:20.2 毛重:22.2=KG,

A4				普通公差								
A3				COMMON TOLERANCE :								
A2				UP TO 5	±0.20	单位	mm	投影	Ac Inlet C14型	品名	比例	Free
A1				ABOVE 5 TO 30	±0.30	UNIT		PROJECTED		PRODUCT NAME	SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	绘图	金泽杰	核对	张	型号	/DB-14	
						日期	2022/2/19	核准	同培	料号	DB-14-1F-ZP	
						DATE		APPROVAL BY		PART NO.		


**东莞市溪榜电子有限公司**  
 DONG GUAN XI BANG ELECTRONI CS CO., LTD.