



Rating:
 15A 250V AC UL cUL
 10A 250V AC VDE 3C KC
 Insert And Extract Force: 20N~50N
 Operating Life: ≥6000 cycles
 Withstand Voltage: Between all terminals:2500VAC(50-60Hz)1min
 Terminals to Base:3750V AC(50-60Hz)1min
 Leakage Current:1mA
 Insulation Resistance:≥100MΩ 500V DC
 Body Materil: NYLON 66 94V-0

序号	名称	材料	处理	数量	备注
1	DB-14-3P8塑料件	环阻PA66	黑色	1	
2	DB-14-PL (L) 长插销	黄铜	镀镍	1	Plating Thickness 40u" -80u"
3	DB-14-PS (S) 短插销	黄铜	镀镍	2	Plating Thickness 40u" -80u"
4	DB-14-S5	黄铜	镀锡	1	Plating Thickness >80u"
5	DB-14-5S	黄铜	镀锡	2	Plating Thickness >80u"

55*43*23.5cm箱, 50只*36吸盒装=1.8k件, 净重:15.7 毛重:18.2=KG,

普通公差:
 COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°



东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV.	DATE	REVISION DESCRIPTION	ISSUE	单位	mm	投影	品名	Ac Inlet C14型	比例	Free
				UNIT		PROJECTED	PRODUCT NAME		SCALE	
				绘图	金泽杰	核对	张彦龙	型号	/DB-14	
				DRAWN BY		CHECKED BY		料号		
				日期	2021/11/25	核准	周培雷	PART NO.	DB-14-3P8-S55 (2.0)-ZP	
				DATE		APPROVAL BY				