



Rating:  
 7A 125V AC UL cUL  
 2.5A 250V AC VDE 3C KC  
 Insert And Extract Force: 20N~50N  
 Operating Life: ≥6000 cycles  
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min  
 Terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current: 1mA  
 Insulation Resistance: >100MΩ 500V DC  
 Body Material: PC 94V-2~0

序号	名称	材料	处理	数量	备注
1	DB-8-5B塑料件	PC	黑色	1	
2	DB-8-R1空心针	黄铜	镀锡	2	Plating Thickness >80u''

55\*32\*25cm箱, 140只\*30吸盒装=4.2k件, 净重:9.7 毛重:11.7=KG,

普通公差:  
 COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°

**XB** 东莞市溪榜电子有限公司  
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV.	DATE	REVISION DESCRIPTION	ISSUE	单位	mm	投影	品名	Ac Inlet C8型	比例	Free
				UNIT		PROJECTED	PRODUCT NAME		SCALE	
				绘图	金泽水	核对	张军龙	型号	/DB-8	
				日期	2022/2/13	核准	周培雷	料号	DB-8-5BR1-ZP	
				DATE		APPROVAL BY	PART NO.			