




MRK.	DATE	REVISION	SIGN
△			

SPECIFICATION


- Rating : 100mA, DC 42V (Switching)
400mA, DC 42V (None-Switching)
- Contact Resistance : 80mΩ Max
- Insulation Resistance : 100MΩ Min at DC 250V
- Operating Force : 120±30gf Max
- Life cycle : 25,000 steps
- Sealing : IP67 (Dust & Water proof)
- Packing : 70pcs Tube / 1,300pcs Reel Packing






P.C.B DIMENSION (Top View)



		Real Coded					
		C	1	2	4	8	
16 P o s i t i o n	0	●					0
	1	●	●				1
	2	●		●			2
	3	●	●	●			3
	4	●			●		4
	5	●	●		●		5
	6	●		●	●		6
	7	●	●	●	●		7
	8	●				●	8
	9	●	●			●	9
	10	●		●		●	A
	11	●	●	●		●	B
	12	●			●	●	C
	13	●	●		●	●	D
	14	●		●	●	●	E
	15	●	●	●	●	●	F



ACTUATOR



DRAW/DESIGNED	CHECKED	APPROVED		G.TOL ±0.3	TITLE	ROTARY DIP SWITCH	
JUN.YANG	DONG.PANG	LIANG.WU		UNIT mm	SCALE 2:1	MODEL	NO. XB-MSDR-16UM
2022-11-09	2022-11-09	2022-11-09		SIZE A4	DRAW NO.	XB-MSDR-16UM	03
DONG GUAN XI BANG ELECTRONICS CO., LTD							