



P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:

- 1.Current Rating: 0.5 Amperes
- 2.Contact Resistance: 50 mΩ Max
- 3.Dielectric Withstanding Voltage: AC 100 V
- 4.Insulation Resistance: 100 MΩ Min
- 5.Operating Temperature: -25°C ~ 65°C

Material:

- 1.Housing: High Temperature Thermal Plastics,UL 94V-0
- 2.Contact: Phosphor Bronze
- 3.Shell: Phosphor Bronze

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer

X3 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | | |
|--------------|----------|-----------|----------|----------------------|
| DRAWN BY: | DATE | MAT'L | TITLE | CONNECTOR |
| Jack Lu | 06/23/15 | | | |
| CHECKED BY: | DATE | FINISH | MODLE | MINI USB AB 型 前插後貼無柱 |
| Jacky Chen | 06/23/15 | | | |
| APPROVED BY: | DATE | SCALE | DWG NO. | MUSB-10P-SD1-S165 |
| Tony Kao | 06/23/15 | 1 : 1 | PART NO. | MUSB-10P-SD1-S165 |
| | | SHEET NO. | 1 of 1 | |
| | | | | SIZE A4 |
| | | | | VER R |