


P.C.B LAYOUT MOUNTING PATTERN



SUA-110V16Ax-x-S236

SHELL :	COLOR :
Blank : Brass	Black: B
I : SPCC	White : W

SPECIFICATIONS

Electrical:

- 1.Rating: 30V DC, 1.5A
- 2.Contact Resistance: 30 mΩ Max
- 3.Dielectric Withstanding Voltage: 500 V AC / 1 minute
- 4.Insulation Resistance: 1,000 MΩ Min

Material:

- 1.Housing: PBT
- 2.Contact: Brass
- 3.Shell: Brass / Spcc


Finish:

- 1.Contact: Plated Gold in Mating Area ;  
Tin Plated on Solder Balls ;  
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer



TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	09/11/20			
CHECKED BY:	DATE	FINISH	MODLE	USB AF 180度直立式 H10.5, 無捲邊 腳距 2.2mm
Jacky Chen	09/11/20			
APPROVED BY:	DATE	SCALE	DWG NO.	SUA-110V16Ax-x-S236
Tony Kao	09/11/20	1 : 1	PART NO.	SUA-110V16Ax-x-S236
		SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE