








P.C.B LAYOUT MOUNTING PATTERN



CIRCUIT



PIN NO.	PIN ASSIGNMENT
1#	DAT2
2#	CD/DAT3
3#	CMD
4#	VDD
5#	CLK
6#	VSS
7#	DAT0
8#	DAT1

- 1) MATERIAL:
HOUSING:LCP
CONTACT:BRASS
SHIELDED:STAINLESS STEEL
- 2) FINISH:
CONTACT: GOLD PLATING ON CONTACT AREA
PLATING ON SOLDER TAILS
NICKEL UNDERPLATING OVER ALL
SHIELDED: NICKEL UNDERPLATING OVER ALL
- 3) PRODUCT SPECIFICATIONS:
CURRENT RATING: 0.5A
INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE: 40mΩ MAX
WITHSTANDING VOLTAGE: 500 V AC/MIN
OPERATION TEMPERATURE: -20° TO +60°



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 05/21/20
DATE: 05/21/20
DATE: 05/21/20

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

CONNECTOR
MICRO SD Card 8+2pin
SD-TF05-N5B10-S304
SD-TF05-N5B10-S304

SIZE
A4
VER
R3

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新圖面	Jack	052120
2	更新尺寸標示	Jack	080218
1	更新圖面	Jack	050418