



手柄位置及导通端子示意图

注意: ①-⑩尺寸的重点检验尺寸

Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.
 1.5 A max. @ 250 VAC.
 MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC
 100mA for both silver.
 INSULATION RESISTANCE: 1000 MΩ min.
 DIELECTRIC STRENGTH: 1000 VAC min.
 OPERATING TEMPERATURE: -30°C to +85°C.

Materials

CASE: PPA (UL 94V-0)
 HOUSING: Stainless Steel.
 ACTUATOR: Alloy, nickel plated.
 BUSHING: Alloy, nickel plated.
 CONTACT/TERMINALS: Copper alloy silver plated.
 RoHS

	POS. 1	POS. 2	POS. 3
Model NO.			
102	ON	NONE	ON
SCHEMATIC		N/A	

东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

公差 TOLERANCES		. X ± 0.4 . XX ± 0.25		角度 ± 5°		UNIT 单位 mm	SCALE 1:1					
版本 VERSION	A0	比例尺 SCALE	NONE	日期 DATE	2021.9.23	TITLE 图名	Sub-Miniature Toggle Switch					
核准 APPROVED BY	FEI. LENG. HE	核对 CHECKED BY	JIE. HAI. LAI	绘图 DRAWN BY	PENG. GAO	DWG NO. 料号						
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY	FEI. LENG. HE	CHECKED BY	JIE. HAI. LAI	DRAWN BY	PENG. GAO	PART NO. 型号	XB-ST-0-102-003-RS	