


安装孔尺寸



手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
103	ON	OFF	ON
SCHEMATIC		OPEN	

标注: ①-⑦ 尺寸的重点检验尺寸

### Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.  
 1.5 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1000 VAC min.  
 OPERATING TEMPERATURE: -25°C to +85°C.

### Materials

CASE: PPA (UL 94V-0)  
 CAP: PA66  
 HOUSING: Stainless Steel.  
 ACTUATOR: Alloy, nickel plated.  
 BUSHING: Alloy, nickel plated.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS



				公差 TOLERANCES				.X± 0.4 .XX± 0.25		角度 ± 5°		UNIT 单位 mm	SCALE 1:1	
				版本 VERSION	A0	比例尺 SCALE	NONE	日期 DATE	2021.9.23	TITLE 图名		Sub-Miniature Toggle Switch		
				核准 APPROVED BY	FEI.LONG.HE	核对 CHECKED BY	JIE.HAI.LAI	绘图 DRAWN BY	PENG.GAO	DWG NO. 料号				
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	PART NO. 型号		XB-ST-0-103-002-RS								