



RECOMMENDED PCB LAYOUT
TOL (± 0.05)

性能:

额定电流: 2.0A

额定电压: 12V

耐电压: 500V

接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -40℃ ~ +85℃

塑件(材质): LCP黑色

接触点(材质): 铜合金, 触点镀金3U

使用寿命: 3000次以上

Pin数	PART NO.	DIM A	DIM B	DIM C
2Pin	XB-BC-24-2PD260-L	4.0	2.0	
3Pin	XB-BC-24-3PD260-L	6.0	4.0	2.0
4Pin	XB-BC-24-4PD260-L	8.0	6.0	4.0
5Pin	XB-BC-24-5PD260-L	10.0	8.0	6.0
6Pin	XB-BC-24-6PD260-L	12.0	10.0	8.0
7Pin	XB-BC-24-7PD260-L	14.0	12.0	10.0
8Pin	XB-BC-24-8PD260-L	16.0	14.0	12.0

版本REV	更新标记REV IS TONNOTE	日期DATE	未注公差 TOLERANCE
			X. ±0.35
			X.X ±0.25
绘制DRAWN	PENG. GAO		X.XX ±0.15
设计DES' D	PAN. HE		X.XXX ±0.05
审核CHK' D	JIE. HAI. LAI	视图方法 PROJECTION	
批准APPV' D	FEI. LONG. HE		

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONI CS CO., LTD.

电池连接器

品名ARTICLE:
图号MODEL:
4P-2.0PH-2.6H-L

A4

比例SCALE:

单位UNIT: mm

页码SHEET: 共1页 第1页