


ROHS



Product specifications:
 Rating: 5A 250VAC;; 2A 36VDC;
 Contact Resistance: 50mQ Max;
 Dielectric Strength: 1500VAC For 1 minute;
 Total Travel: 1.5±0.5mm
 Operating Force: 600±200gf
 Mechanical Life: 20000 Cycles;
 Load Life: 50000 cycles;
 Openrating Temperature: -20 ℃~70 ℃
 Function:OFF- (ON) ON-OFF

安裝尺寸Diameter: $\Phi 19$ mm
 燈珠顏色Color: R G Y B W
 開關額定值Switch Rating: 5A/250VAC
 開關組合Contact Configuration: 1NO1NC(11)/2NO2NC(22)
 操作類型Operation Type: 自復型Momentary
 自鎖型Maintained(Z)
 頭部形狀The Front Shape: 平面 Flat
 帶燈方式Lamp type: 單點帶燈Dot Illuminated(LED)
 外殼材料The Crust Material: 不銹鋼Stainless steel
 防護等級IP Degree: IP67, IK10

W6	白色	5.0	6.0	9.0	15
U6	藍色	5.0	6.0	9.0	15
G6	純綠色	5.0	6.0	9.0	15
Y6	黃色	5.0	6.0	9.0	15
R6	紅色	5.0	6.0	9.0	15
W3	白色	2.8	3.0	3.4	15
U3	藍色	2.8	3.0	3.4	15
G3	純綠色	2.8	3.0	3.4	15
Y2	黃色	1.8	2.0	2.4	15
R2	紅色	1.8	2.0	2.4	15
燈發光顏色 X Emitted color X	最小	一般	最大	額定 電流 (mA)	
	順向電壓(V)				

LED Specifications

LED 类型	双向LED灯珠（交直流通用）			U3	藍色	2.8	3.0	3.4	15
寿 命	40000小时（参考值）			G3	純綠色	2.8	3.0	3.4	15
额定电压	AC/DC12V	AC/DC24V	AC/DC110V	Y2	黃色	1.8	2.0	2.4	15
	AC/DC36V	AC/DC48V	AC/DC220V	R2	紅色	1.8	2.0	2.4	15
额定电流	约15mA		约3mA	灯发光颜色 X Emitted color X		最小	一般	最大	额定 電流 (mA)
降压方式	采用3V灯，需内置电阻			順向電壓(V)					

MATERIAL:

Actuator: SUS ;
 Top Base: SUS;
 Buttom Base:PA66+GF ;
 Terminal: Brass,Silver plated ;
 Nut: Brass, Ni plated .


The material contained in this drawing is the property of XiBang. Any use other than that specfically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO.,LTD

TITLE : METAL PUHS BUTTON SWITCH

MODEL : XB-PBM19-13Z-DG3-B1-S



TOLERANCE
 $\leq 1.5\text{mm} \pm 0.1$
 $> 1.5\text{mm} \pm 0.2$
 $> 10\text{mm} \pm 0.3$

ANGLE
 $\pm 2^\circ$

UNIT : MM	DWN.	ZENQ. CHEN	DATE	
SCALE : 3 : 1	CHK'D	PENG. GAO	DATE	
VBRSION	01	APPD.	FEI. LONG. HE	DATE

7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK
NO.	PART NAME	MATERIAL	QTY.	FINISHING