







ROHS



Switch Specifications
 Rating: 5A 250VAC ;
 2A 36VDC ;
 Degree of protection: IP67 ;
 Contact Resistance: 50mΩ Max. ;
 Dielectric Strength: 1000VAC For 1 minute ;
 Total Travel: 2.8±0.5mm ;
 Operating Force: 600±200gf ;
 Mechanical Life: 200,000 cycles ;
 Load Life: 50,000 cycles ;
 Operating Temperature: -20° C~85° C ;
 Function: OFF-(ON)



MATERIAL:
 Actuator: SUS ;
 Top Base: SUS;
 Bottom Base: PA66+GF ;
 Terminal: Brass, Silver plated ;
 Nut: Brass, Ni plated .


Panel Thickness: 10mm MAX.

LED Specifications

W6	白色	5.0	6.0	9.0	15
U6	蓝色	5.0	6.0	9.0	15
G6	纯绿色	5.0	6.0	9.0	15
Y6	黄色	5.0	6.0	9.0	15
R6	红色	5.0	6.0	9.0	15
W3	白色	2.8	3.0	3.4	15

LED 类型	双向LED灯珠（交直流通用）			U3	蓝色	2.8	3.0	3.4	15
寿 命	40000小时（参考值）			G3	纯绿色	2.8	3.0	3.4	15
额定电压	AC/DC12V	AC/DC24V	AC/DC110V	Y2	黄色	1.8	2.0	2.4	15
	AC/DC36V	AC/DC48V	AC/DC220V	R2	红色	1.8	2.0	2.4	15
额定电流	约15mA		约3mA	灯发光颜色 X Emitted color X	最小	一般	最大	额定 电流 (mA)	
降压方式	采用3V灯，需内置电阻				顺向电压(V)				

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing is subjected to change for improvement without prior notice.

 Switch Connector		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD				 TOLERANCE ≤1.5mm±0.1 > 1.5mm±0.2 >=10mm±0.3 ANGLE ±2°													
		TITLE : METAL PUHS BUTTON SWITCH		MODEL : XB-PBM22-12Z-F-PG3-Z6				7		SPRING		STEEL WIRE		1		NATURE			
UNIT : MM		DWN.		ZENQ. CHEN		DATE				6		STEEL BALL		STEEL		1		NATURE	
SCALE : 3 : 1		CHK'D		PENG. GAO		DATE				5		BOARD		PHENOLIC RESIN		1		NATURE	
VERSION		01		APPD.		FEI. LONG. HE		DATE		4		CONTACT CLIP		PBS STRIP		2		Ag PLATED	
										3		FRAME		IRON STRIP		1		Ni PLATED	
										2		TERMINAL		BRASS STRIP		8		Ag PLATED	
										1		KNOB		POM		1		BLACK	
										NO.		PART NAME		MATERIAL		QTY.		FINISHING	