





ROHS



TOGGLOE SWITCH 1P2T



SPECIFICATION (INITIAL)

RATING:	DC	50V	0.5A
CONTACT RESISTANCE:	Not more than 30m Ω		
INSULATION RESISTANCE:	500M Ω at 500V DC		
WITHSTAND VOLTAGE:	AC 500V for 1 min		
OPERATION FORCE:	350 $\pm$ 100g		
SWITCHING LIFE:	10000cycles(6-10c/m loading)		


The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing is subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO.,LTD

TITLE : HORIZONTAL SLIDE SWITCH

MODEL : XB-TS-12F01



TOLERANCE
 $\leq 1.5\text{mm} \pm 0.1$
 $> 1.5\text{mm} \pm 0.2$
 $> 10\text{mm} \pm 0.3$

ANGLE
 $\pm 2^\circ$

NO.	PART NAME	MATERIAL	QTY	FINISHING
7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK