



SPECIFICATION (INITIAL)				
RATING:	DC	50V	0.5A	
CONTACT RESISTANCE:	Not more than 30mΩ			
INSULATION RESISTANCE:	500MΩ at 500V DC			
WITHSTAND VOLTAGE:	AC 500V for 1 min			
OPERATION FORCE:	300 ± 100g			
SWITCHING LIFE:	10000cycles(6-10c/m loading)			

The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD

TITLE : **XB SLIDE SWITCH**
MODEL : **XB-SS-13F18X**



TOLERANCE
 ≤1.5mm±0.1
 > 1.5mm±0.2
 >=10mm±0.3

ANGLE
 ±2°

UNIT : MM	DWN.	ZENQ. CHEN	DATE	
SCALE : 3 : 1	CHK'D	PENG. GAO	DATE	
VBRSION	01	APPD.	FEI. LONG. HE	DATE

NO.	PART NAME	MATERIAL	QTY	FINISHING
7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK