

ROHS

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO.,LTD

TITLE : HOOK SWITCH

MODEL : HS-22L07

TOLERANCE
<=1.5mm ± 0.1
> 1.5mm ± 0.2
>=10.0mm ± 0.3

ANGLE TOL
± 2°

9	RED OIL	R001	1	RED
8	CONTACT OIL	1000#	1	NATURE
7	SLIDER	PBT	1	BLACK
6	SPRING	SUS	1	NATURE
5	CONTACT	PBS STRIP	2	Ag CLAD
4	TERMINAL	BRASS STRIP	6	Ag PLATED
3	CASE	PBT	1	NATURE
2	COVER	POM	1	BLUE
1	KNOB	POM	1	BLUE
NO.	PART NAME	MATERIAL	QTY.	FINISHING

ROHS

GENERAL TOLERANCES: ±0.05
P. C. B MOUNTING

SHORTING
SCHEMATIC

SHORTING TYPE		CITCUIT DIAGRAM	
PUSH DOWN	(A) (C)	ON	OFF
	(B) (C)	OFF	ON
	(D) (F)	ON	OFF
	(E) (F)	OFF	ON
7.85		5.2	4.9
TRAVEL POSITION (X)		4.6	4.3
		1.9	
		TOLERANCE: ± 0.50mm	
SHORTING TYPE		CITCUIT DIAGRAM	
RELEASE	(A) (C)	ON	OFF
	(B) (C)	OFF	ON
	(D) (F)	ON	OFF
	(E) (F)	OFF	ON
7.85		5.5	5.2
TRAVEL POSITION (X)		4.9	4.6
		1.9	
		TOLERANCE: ± 0.50mm	