



# Specifications

Current Rating:1.0Amp

Insulation Resistance:500MΩMin.

Dielectric Withstanding Voltage:250VAC

Contact Resistance:100mΩMax.

Operating Temperature:-40°C to +105°C

## Materials

Contact Material:Phosphor Bronze

Insulator Material:High Temperature

Thermoplastic, UL 94V-0 LCP or

the equivalent material

★ All materials must meet GREENCONN hazardous substances control standards.

★: Critical Characteristics, indicates product characteristics, functionalities, and manufacturing processes regarding to customer's specifications

★: Safety Features indicates product characteristics, functionalities, and manufacturing processes complying to legal regulations stated by local government

Recommended P.C.Board Layout  
(Tolerance:±0.05)

## Ordering Information

G BZZ203 - 04 XX A 001 C 1 S X

No. of Pins per Row  
04

Standard Plating  
08=5u"gold on contact/  
gold flash on other area

Color  
1=Black

Standard Packing  
H=Acetate tape+Tape&Reel

**东莞市溪榜电子有限公司**  
DONG GUAN XI BANG ELECTRONIC CO., LTD.

3RD.ANG  
PROJ.  
PAGE. 1/1

### GENERAL TOLERANCE

X.*±5.0"	X.±0.30
.X*±3.0"	.X±0.25
.XX*±2.0"	.XX±0.15
.XXX*±1.0"	.XXX±0.10

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

XB-CBZZ-203

PART NO.

XB-CBZZ-203

TITLE.

6.50mm PITCH MALE  
FLOATING CONNECTOR  
MATING H25.00mm