


线路图
CIRCUIT DIAGRAM








电流电路
CURRENT CIRCUIT

CIRCUIT:003

位置POSITION	电路CIRCUIT
1(INITIAL)起始	OFF
2	C2+3
3	C1+1,C2+3
4	C1+1+2,C2+3

- 1.滑动开关型号 SLIDE SWITCH MODEL:KND-2-3BS003-R2
2.焊线端子 SOLDER CONNECTOR TYPE;
单刀四掷, 多回路 SINGLE POLE FOUR THROW , MULTI-CIRCUIT
3.额定值 RATING: 16(4)A 125/250VAC μ T105 (UL,KC)
10(2)A 125/250VAC μ T85 (UL,KC,CQC,ENEC17,NEMKO)
10A 250VAC μ T85 (CE)
7(2)A 250VAC μ T85 (UL,CQC,ENEC17;NEMKO)
5(1)A 250VAC μ T85 (UL,CQC,ENEC17;NEMKO)
4.接触电阻 CONTACT RESISTANCE: <50m Ω (INITIAL)
5.绝缘电阻 INSULATION RESISTANCE: $\geq$ 100M Ω (DC500V/1MIN)
6.介电强度 DIELECTRIC STRENGTH: 1500V /0.5mA /1MIN
7.机械寿命 MECHANICAL LIFE: >50000 CYCLES
8.电气寿命 ELECTRICAL LIFE: >10000 CYCLES
9.端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX350°C, 3S
10.操作力 OPERATION FORCE:550 $\pm$ 200gf
11.所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT



The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.

 Switch Connector		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO.,LTD												
		TITLE : XB SLIDE SWITCH												7
MODEL : XB-KND-2-3BS003-R2 四位拨码开关大电流16A 电风吹4位滑动开关5脚10A				6		STEEL BALL	STEEL	1	NATURE					
UNIT : MM		DWN.	ZENQ. CHEN	DATE	TOLERANCE <=1.5mm±0.1 > 1.5mm±0.2 >=10mm±0.3		ANGLE ±2°		5		BOARD	PHENOLIC RESIN	1	NATURE
SCALE : 3 : 1		CHK'D	PENG. GAO	DATE					4		CONTACT CLIP	PBS STRIP	2	Ag PLATED
VERSION 01		APPD.	FEI. LONG. HE	DATE					3		FRAME	IRON STRIP	1	Ni PLATED
									2		TERMINAL	BRASS STRIP	8	Ag PLATED
									1		KNOB	POM	1	BLACK
									NO.		PART NAME	MATERIAL	QTY.	FINISHING