





ROHS



PCB MOUNTING HOLE ARRANGEMENT



线路/ Circuit



- 滑动开关型号 SLIDE SWITCH MODEL: SFD-1-24DAP
- PCB端子 PCB TYPE;
双刀双掷 DOUBLE POLE DOUBLE THROW)
- 额定值 RATING: 10(2)A 250VAC μ T85 (ENEC17;NEMKO;CQC)
- 接触电阻 CONTACT RESISTANCE: <50m Ω (INITIAL)
- 绝缘电阻 INSULATION RESISTANCE: $\geq 100\text{M}\Omega$ (DC500V/1MIN)
- 介电强度 DIELECTRIC STRENGTH: 1500V/5mA/1MIN
- 机械寿命 MECHANICAL LIFE: >50000 CYCLES
- 电气寿命 ELECTRICAL LIFE: >10000 CYCLES
- 端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX350°C, 3S
- 操作力 OPERATION FORCE: 850 $\pm$ 300gf
- 所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT


The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD

TITLE : XB SLIDE SWITCH

MODEL : XB-SFD-1-24DAP大电流开关4位2P4T 大电流4档电器开关10脚



TOLERANCE
<=1.5mm $\pm$ 0.1
> 1.5mm $\pm$ 0.2
>=10mm $\pm$ 0.3

ANGLE
 $\pm 2^\circ$

UNIT : MM	DWN.	ZENQ. CHEN	DATE	
SCALE : 3 : 1	CHK'D	PENG. GAO	DATE	
VBRSION	01	APPD.	FEI. LONG. HE	DATE

7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK
NO.	PART NAME	MATERIAL	QTY.	FINISHING