






Specifications
Current Rating:3.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:600VAC
Contact Resistance:20mΩMax.
Operating Temperature:-40°C to +105°C
Materials
Contact Material:
Phosphor Bronze
Insulator Material:
PBT(Not resistant to high temperature),
Nylon(High temperature resistance),
LCP(High temperature resistance),
UL 94V-0
All materials must meet XI BANG
hazardous substances control standards.



Recommended P.C.Board
Hole Layout
(Tolerance:±0.05)



No. of PIN/ROW	Dimension Information	
	M	L
02	2.54	5.58
03	5.08	8.12
04	7.62	10.66
05	10.16	13.20
06	12.70	15.74
07	15.24	18.28
08	17.78	20.82
09	20.32	23.36
10	22.86	25.90
11	25.40	28.44
12	27.94	30.98
13	30.48	33.52
14	33.02	36.06
15	35.56	38.60
16	38.10	41.14
17	40.64	43.68
18	43.18	46.22
19	45.72	48.76
20	48.26	51.30
21	50.80	53.84
22	53.34	56.38
23	55.88	58.92
24	58.42	61.46
25	60.96	64.00
26	63.50	66.54
27	66.04	69.08
28	68.58	71.62
29	71.12	74.16
30	73.66	76.70
31	76.20	79.24
32	78.74	81.78
33	81.28	84.32
34	83.82	86.86
35	86.36	89.40
36	88.90	91.94
37	91.44	94.48
38	93.98	97.02
39	96.52	99.56
40	99.06	102.10


Ordering Information

XB-PM-F-254-211

- Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple
- Water code
- No. of Pins per Row
02~40
- Positioning column information
A=No locating post
B=Round post
C=Square post
- Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin
- Pin length
See the drawing
- Insulator Material
A=PBT
R=Nylon(Halogen Free)
C=LCP
- Color
1=Black
2=White
3=Yellow
E=Beige
- Contact Material
A/S/K/T=Phosphor Bronze
- Packing code
C=Tube
D=Tape&Reel
E=Cap+Tube
F=Cap+Tape&Reel
G=Acetate Tape+Tube
H=Acetate Tape+Tape&Reel

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

GENERAL TOLERANCE	
X.*±5.0°	X.±0.30
.X*±3.0°	.X±0.25
.XX*±2.0°	.XX±0.15
.XXX*±1.0°	.XXX±0.10



DWG. NO.
XB-PM-F-254-211
PART NO.
XB-PM-F-254-211

TITLE.
2.54 FEMALE HEADER
DUAL ROWS DIP TYPE
CONNECTOR

REV.	UNIT.	SCALE.	PAGE.
01	mm	4:1	1/1