



| 5. | Terminal | Brass | 1 | Nickel Plated |
|-----|-----------------|----------|------|---------------|
| 4. | Ground Terminal | Brass | 1 | Nickel Plated |
| 3. | Housing | PVC | 1 | Black Color |
| 2. | Outer Sleeve | Brass | 1 | Nickel Plated |
| 1. | Insulator Ring | POM | 1 | Yellow Color |
| NO. | Description | Material | Q'TY | Finish |

| | | | | | |
|---|------------|-----|------|------|---------|
|  东莞市溪榜电子有限公司 Switch Connector DONG GUAN XI BANG ELECTRONICS CO., LTD | DATE | DWN | CHKD | APVD | MANAGER |
| | 06.14.2006 | | | | |

| | | |
|--|------------------------------------|-------------|
| PART NAME : AEESMBLY TYPE DC PLUG ϕ 5.0X ϕ 1.0 | PART NUMBER : XB-DC-T-901PTN00000G | VERSION:4.0 |
| TOLERANCE : 0>1.0:±0.1 1.0>6.0:±0.2 6.0>12.0:±0.3 12.0>25.0:±0.4 25.0>:±0.5 | UNIT:mm | SCALE:1/1 |

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

RoHS Compliant For Reference
 僅供參考