

Material:

- * Insulation: Nylon 66 UL 94V-2
- * Contact: Brass

Ordering Code:

CI23 ** P 1 V 0 0
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 - 1= 3.05μm(120μ") Min. Tin over 0.76μm(30μ") Nickel
 - 2= Gold flash plated over 1.27μm(50μ") Nickel
- ⑤ Tail Style: V= Straight
- ⑥ Color: 0= Nature, 5= Yellow
- ⑦ Option: 0= Standard


△ 2 THROUGH 5 CIRCuits

△ 6 THROUGH 12 CIRCuits

A = 2.5 x No. of Spaces

B = A + 2.5

* Available in 2 through 12 circuits



Recommended P.C. Board Layout

Halogen-Free

Tin-Lead Process

RoHS Compliant

| | | | | | | | | |
|-----|-------|-----------|---------------------|-------------------|-----------|--------------------------------------|---------------------------------------|---|
| ④ | | | | | DATE | UNIT: mm / inch | TITLE: 2.50MM(.098") STRAIGHT HEADERS | 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONI CS CO., LTD. |
| ③ | | | | DRAWN BY: Sandy | 12/21-06' | TOLERANCE UNLESS OTHERWISE SPECIFIED | MATERIAL: | |
| ② | Sandy | 12/21/06' | ECN06487 | ENGINEER: Eisley | 12/22-06' | .X ± 0.30/.012 X' ± 1" | FINISH: | DRAWING NO. CI2302SD |
| ① | Jim | 5/17/06' | ECR06036-0/ECN06143 | CHECKED BY: David | 12/22-06' | .XX ± 0.20/.008 .X' ± | | DRAWING NO. CI2302SD |
| SYM | NAME | DATE | REVISIONS | APPROVED BY: Alex | 12/22-06' | .XXX ± 0.10/.004 .XX' ± | SCALE 2 / 1 | SHEET 1 OF 1 |