

A = 5.00 * No. of Spaces

B = A + 5.00

* Available in 2 through 20 circuits

Recommended P.C. Board Layout

Material:

* Insulation: Glass filled polyester UL 94V-0

* Contact: Brass


Ordering Code:

CI78 ** P 1 V 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
CI78= 5.0mm center spacing
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 1= 3.05μm(120μ") Min. Tin
 over 0.76μm(30μ") Nickel
 2= Gold flash plated over
 1.27μm(50μ") Nickel
 3= 0.38μm(15μ") Gold plated
 over 1.27μm(50μ") Nickel
 4= 0.76μm(30μ") Gold plated
 over 1.27μm(50μ") Nickel
- ⑤ Tail Style: V= Straight
- ⑥ Option: 00= Color White(Nature)

Tin-Lead Process

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: 5.00MM(.197") BOARD MOUNT PIN HEADER	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONI CS CO., LTD.
3				DRAWN BY: Betty	09/28-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2				ENGINEER: David	09/28-01'	.X ± 0.38/.015 X' ± 1'	FINISH:	DRAWING NO. CI7801SC
1				CHECKED BY: David	09/28-01'	.XX ± 0.25/.010 X' ±		PART NO. CI78**P1V00
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	09/28-01'	.XXX ± 0.15/.006 .XX' ±	SCALE 2 / 1	SHEET 1 OF 1