



Material:  
 Insulator: Glass filled Polyester UL 94V-0  
 Contact: Copper alloy  
 Shell: Steel, Nickel plated as standard  
 High power Contact :  
 Brass with Gold plated  
 \* For Lead Free Wave Flow Process

### Ordering Code

11W1 S P V 3 2 1 40 D00  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: S= Receptacle
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: V= Straight Dip type
- ⑤ High power contact plating:  
 2= Gold flash plated over Nickel  
 3= 15μ" Gold plated over Nickel  
 4= 30μ" Gold plated over Nickel  
 5= 50μ" Gold plated over Nickel
- ⑥ Signal contact plating:  
 2= Gold flash plated over Nickel  
 3= 15μ" Gold plated over Nickel  
 4= 30μ" Gold plated over Nickel
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 40= 40A
- ⑨ Mounting Style:  
 000= With Ø3.05mm holes on shell  
 B00= Riveted #4-40 UNC open nuts on front shell  
 C00= Riveted #4-40 UNC open nuts on rear shell  
 D00= Riveted #4-40 UNC ground stand-off on rear shell(standard)

Mounting Style		Lead Free Process		RoHS Compliant			
Code	000	Code	B00	Code	C00	Code	D00
			DIM. L= 4.0mm		DIM. L= 4.0mm		DIM. L= 7.0mm

④					DATE	UNIT: mm / inch	TITLE: 11W1 40A HIGH POWER FEMALE D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)	<b>东莞市溪榜电子有限公司</b> DONG GUAN XI BANG ELECTRONICS CO., LTD
③				DRAWN BY: Karen	1/09-18'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Sun	1/10-18'	.X ± 0.30/.012 X' ± 1"	FINISH:	
①	Karen	1/09-18'	ECNT117262/ECRT117074	CHECKED BY: Eisley	1/11-18'	.XX ± 0.20/.008 X' ±	DRAWING NO. <b>11W110SC</b> PART NO. <b>11W1SPV***40*00</b>	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	1/11-18'	.XXX ± 0.10/.004 XX' ±	SCALE 2 / 1 SHEET 1 OF 1	