



Material:

Insulator: Glass filled Polyester UL 94V-0

Contact: Brass

△ Shell: Steel, Nickel plated as standard

Ordering Code

13W3 P0 S0 A 100 000
 ① ② ③ ④ ⑤ ⑥

① Series No.

② Connector Type:

P0= Plug

③ Contact tail Style:

S0= Solder Cup type

④ Singal Contact Plating:

A= Seletive Gold flash plated over Nickel

B= Seletive 15μ" Gold plated over Nickel

C= Seletive 30μ" Gold plated over Nickel

⑤ Insulator Color:

100= Black

600= Green

⑥ Mounting Style:

000= With 3.05mm holes on shell

A00= Riveted #4-40 UNC close nuts on front shell

B00= Riveted #4-40 UNC open nuts on front shell

C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style

RoHS Compliant

Code	000	Code	A00	Code	B00	Code	C00
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

④					DATE	UNIT: mm / inch	TITLE: 13W3 MALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD
③				DRAWN BY: Karen	1/10-18'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Sun	1/11-18'	.X ±0.30/.012 X' ± 1'	FINISH:	DRAWING NO. 13W301SD PART NO. 13W3P0S0**00*00
①	Karen	1/10-18'	ECNT117262/ECRT117074	CHECKED BY: Eisley	1/11-18'	.XX ±0.20/.008 X' ±		SCALE 2 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	1/11-18'	.XXX ±0.10/.004 X' ±		