



Material:

Insulator: Glass filled Polyester UL 94V-0

Shell: Steel, Tin plated as standard

Ordering Code

C5W5 S0000 100 000
 ① ② ③ ④

- ① Series No.
- ② Connector Type:
S0000= Receptacle
- ③ Insulator Color:
100= Black
600= Green
- ④ Mounting Style:
000= With $\phi 3.05$ mm holes on shell
A00= Riveted #4-40 UNC close nuts on front shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style				RoHS Compliant			
Code	000	Code	A00	Code	B00	Code	C00
		DIM. L= 5.8mm 		DIM. L= 4.0mm 		DIM. L= 4.0mm 	

④					DATE	UNIT: mm / inch	TITLE: C5W5 FEMALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.				
③				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:				DRAWING NO. C5W502SB	PART NO. C5W5S0000*00***
②				ENGINEER: David	10/15-01'	.X ± 0.30/.012 X' ± 1"	FINISH:				SCALE 2 / 1	SHEET 1 OF 1
①				CHECKED BY: David	10/15-01'	.XX ± 0.20/.008 X' ±						
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/15-01'	.XXX ± 0.10/.004 X' ±						