




- Ordering Code

C8W8	S	P	H	3	0	1	20	110
①	②	③	④	⑤	⑥	⑦	⑧	⑨

- ① Series No.
- ② Connector Type: S= Receptacle
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ High power contact plating:
 - 2= Gold flash plated over Nickel
 - 3= 15 μ " Gold plated over Nickel
 - 4= 30 μ " Gold plated over Nickel
 - 5= 50 μ " Gold plated over Nickel
- ⑥ Singal contact plating:
 - 0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 20= 20A
- ⑨ Mounting Style:
 - 000= With $\varnothing$ 3.05mm holes on shell
 - B00= Riveted #4-40 UNC open nuts on front shell
 - C00= Riveted #4-40 UNC open nuts on rear shell
 - I00= Riveted #4-40 UNC ground tabs
with $\varnothing$ 3.2mm holes
 - I10= Riveted #4-40 UNC ground tabs
with board locks(standard)



Mounting Style

Code	000	Code	B00	Code	C00	Code	I00	Code	I10
		DIM. L= 4.0mm 		DIM. L= 4.0mm 		$\phi A=3.2mm$ 			

4						DATE	UNIT: mm / inch	TITLE: C8W8 20A HIGH POWER FEMALE D-SUB CONNECTOR (RIGHT ANGLE BOARD MOUNT TYPE) MATERIAL: FINISH:	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	DRAWING NO.	C8W812SC	PART NO.	C8W8SPH*0*20**
3				DRAWN BY:	Karen	3/20-17'	TOLERANCE UNLESS OTHERWISE SPECIFIED						
2				ENGINEER:	Sun	3/20-17'	$.X \pm 0.30/.012$ $X' \pm .1'$ $.XX \pm 0.20/.008$ $X'' \pm$						
1	Karen	3/20-17'	ECNT117049/ECRT117003	CHECKED BY:	Eisley	3/22-17'	$.XXX \pm 0.10/.004$ $.XX' \pm$						
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Eisley	3/22-17'				SCALE	2 / 1	SHEET	1 OF 1